



For all your temporary surface protection needs, Skudo's got you covered

### Description

The Skudo MT (Medium Traffic) Commercial System provides temporary surface protection on interior commercial construction jobs. It is comprised of a flexible, peelable Concrete Base Coat and the MT (Medium Traffic) Mat, which together create a homogeneous covering that does not permit contaminants or debris to get between it and the substrate it's protecting.

The MT Commercial System protects against mold, impact and light machinery. With the highest level of slip resistance of all the Skudo products, the MT Mat also provides a safe working environment with a non-slip, seamless and stationary work surface. MT Commercial can protect surfaces up to 9 months.

(NOTE: Interior use only)

Once the project is completed, the MT Mat is simply peeled up and disposed of in general site garbage bins.

### Uses

- Protects most surfaces, including freshly placed concrete as early as 21 days.
  - \*Note: This is subject to slab thickness, mix design, weather, etc. Please contact your Skudo Rep to determine suitability
- Protects polished concrete and terrazzo
- Under Scaffolding & Shoring, Light Machinery

### Benefits

- ✓ Reliable surface protection for Medium construction site traffic
  - Spill, stain and water resistance
  - Resistance to impact
  - Antibacterial/Antifungal: Test-verified protection against bacteria and molds that cause infection. (ISO-20743)
- ✓ Safer working surface
  - High slip resistance in wet and dry conditions
  - Seamless and stationary
- ✓ Cleans surface upon peel up removal

Protected in the United States by patent # 10190004





For all your temporary surface protection needs, Skudo's got you covered

### Substrate Suitability

Raw Concrete (Smooth)	Very Good	Tiles - Porcelain	Excellent
Polished Concrete (Sealed)	Excellent	Marble / Stone - Smooth	Excellent
Decorative Concrete	Good	Marble / Stone - Coarse	Very Good
Brushed Concrete	Fair	Epoxy Coated Surfaces	Very Good
Aged Concrete	Good	Primed Steel	Excellent
Acid Washed Concrete	Poor	Fiberglass	Excellent
Stairs	Very Good	Laminate	Good
Terrazzo	Excellent	High Pressure Laminate	Good
Hardwood (Sealed)	Good	Topping/Overlays	Avoid
Tiles - Ceramic	Excellent		

### Product Coverage

<b>MT Mat</b>	800 sq. ft./roll 6.5'W x 123'L
<b>Base Coat</b>	
Smooth/Troweled Surfaces	150 sq. ft./gal
Textured/Medium Broomed finish	as low as 80 sq. ft./gal

The surfaces listed above provide a guide only and vary due to a range of factors. For substrates not listed above, please refer to your Skudo representative. All substrates should be tested for suitability by doing a small spot test. No warranties implied or otherwise are given for the usage of this product.

### Application

The Skudo Commercial System is applied in two steps:

1. The water based Concrete Base Coat is applied using our Notched Squeegee Method. See application sheet for details.
2. The MT Mat is rolled out and pressed into wet Base Coat. For more information on detailed application, please refer to our Website, Product Application Sheet or Label.



### Precautions

- Interior use only.
- Do not dilute.
- Should not be applied to concrete exposed to excessive moisture. Skudo must be kept dry for 24 hours after installation.
- Do not apply if the temperature of the concrete or air temperature is below 40° F (4° C).
- If installing over sealed, guarded or protected concrete or terrazzo, it is critical sealer is fully cured. Dry to the touch is not sufficient. Always consult a Skudo Representative for compatibility.
- If the Commercial System sits in standing water or extremely heavy rainfall or drainage, water can eventually infiltrate and break the adhesion between the protected substrate and Skudo Base Coat. If this occurs, carefully drain or squeegee water off the affected area. Keep traffic off Skudo until it has dried. In most cases the mat will re-adhere to the substrate.
- Once installed, allow all exposed Base Coat to dry completely along the outer edges, then peel up to remove (see below).



**NOTE:** For a detailed explanation of Skudo Commercial Mat System usage, application process and limitations, please see our website which includes step-by-step instructions



Contact PanAmar

For a quote, to place an order, or to learn more about Skudo, visit [www.panamarinc.com](http://www.panamarinc.com) or email us at [sales@panamarinc.com](mailto:sales@panamarinc.com) or call Dan Ferson (760) 443-6621 - Lisa Ferson (619) 921-0318 - Lisa McGuckin (760) 845-1865